Appln. No. 10/621,607 Amdt. dated April 1, 2005 Reply to Office Action dated January 11, 2005

AMENDMENTS TO THE ABSTRACT

Please replace the Abstract with the following amended Abstract, a clean copy of which follows page __ of this paper.

and a seat for opening and closing of the casing. The locking device has a recess formed on an edge of the seat, a buckle downwards protruding from the cover and matching the recess, and a roller parallel-disposed in the recess and pivoted to the seat. The buckle has an accurate arcuate face smoothly against an upper slot of the roller for closing and opening the casing. A direction of lifting of the cover corresponds to a rotation of the roller so that a direction of applied force can be continuously unchanged to achieve an ergonomic effect.--



Appln. No. 10/621,607 Amdt. dated April 1, 2005 Reply to Office Action dated January 11, 2005

REPLACEMENT ABSTRACT

A locking device applies to a casing having a cover and a seat for opening and closing of the casing. The locking device has a recess formed on an edge of the seat, a buckle downwards protruding from the cover and matching the recess, and a roller parallel-disposed in the recess and pivoted to the seat. The buckle has an arcuate face smoothly against an upper slot of the roller for closing and opening the casing. A direction of lifting of the cover corresponds to a rotation of the roller so that a direction of applied force can be continuously unchanged to achieve an ergonomic effect.